Magmex Plus Fire Hose



Externally Elastomeric Coated, All Synthetic, EPDM Rubberlined Fire Hoses

CONSTRUCTION

Circularly woven jacket Coated with specially formulated Elastomeric RED Coating for protection against abrasion, mild chemicals and heat

INNER LINING

Ultra Light weight synthetic EPDM Rubber having low friction loss and very high ozone resistance.

CHARACTERISTICS

- Outer Coating of specially formulated RED POLYMER Resistant against abrasion, heat and mild chemicals
- Flexible compact with small coil diameter
- · Resistant to fungus, rot and mildew
- High Burst and Kink pressure ratings
- Colour : Red

APPLICATIONS

- Fire Brigades
- Power Plants

and other industries

- Railways
- High rise buildings
- Steel Plants
- Sailing Vessels

APPROVALS

- ISI Marked under IS: 636/1988 Type A
- UL-Listed under UL-19 USA
- Lloyds Approved under BS: 6391
- DG Shipping (MMD Approved)
- ISO 9001:2008 Quality Systems
- EIL Approved

Size mm / inches	Max Wt gm / mtr	Working Pressure psi	Proof Pressure psi	Burst Pressure psi
38 / 11/2"	275	260	320	600
51 / 2"	350	260	320	600
63.5 / 21/2"	425	260	320	550
70 / 23/4"	480	260	320	550
76 / 3"	490	260	320	550

AN ISO 9001 - 2008 COMPANY















CHHATARIYA FIRETECH INDUSTRIES

23A SURYODAYA MILLS COMPOUND | 96 TARDEO ROAD MUMBAI 400 034 | INDIA

PH 91 22 23513705 / 23521313 / 23510849 | FAX 91 22 23510400 E-MAIL chhatariya@vsnl.com | URL www.chhatariya.com FACTORY:

89 GIDC ESTATE, MAHUVA 364 290, GUJARAT, INDIA PH +91 2844 228887 / 228749 | FAX 91 2844 246287 E-MAIL cfi_52@yahoo.co.in | URL www.chhatariyafiretech.com